



SPECIFICATION
 Contact Rating : 50mA, 12V DC
 Contact Resistance : 100mΩ max
 Insulation Resistance : 100mΩ min. 500V DC
 Dielectric Strength : 250V AC/1minute
 Travel : 1.2mm
 Operating Temp : -30℃~+85℃
 Storage Temp : -30℃~+80℃

PAPT NO	TC-1117D-X
Operating Force	A: 120gf B: 160gf C: 260gf
Height	II: 5.0

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
③	Terminal	2	2	Brass (0.30t)	Plating silvering	
②	Base	1	1	Pa46		
①	Keystake	1	1	Silica gel		

MARK	DESCRIPTION	DATE	REVISED	APPROVED

units: mm
 tolerance:
 X.X ±0.2mm
 X.XX ±0.1mm
 X.XXX ±0.05mm

UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm	DWG NO.:
APPD		DATE		SIZE: A4	TC-1117D-X
XKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET
				1.0g	1/1
				REVISION	A0