

Preliminary Datasheet

SOD882 Plastic Package Transient Voltage Suppressors ESD Protection Diode

Absolute Maximum Ratings T_A = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
PD	Power Dissipation	150	mW
T _{STG}	Storage Temperature Range	-55 to +125	°C
TJ	Operating Junction Temperature	+125	°C
V _R	DC Reverse Voltage	30	V
I _{F(AV)}	Average Forward Current	200	mA
I _{FSM}	Peak Forward Surge Current (At 8.3ms single half sine-wave) 0.5		А

These ratings are limiting values above which the serviceability of the diode may be impaired.

Specification Features:

- Low Forward Voltage Drop
- Small Surface Mounting Type
- RoHS Compliant
- Green EMC
- Matte Tin(Sn) Lead Finish
- Band Indicates Cathode

Electrical Characteristics T_A = 25°C unless otherwise noted

Symbol	Parameter	Test Condition	Limits		Unit
			Min	Max	Unit
I _R	Reverse Leakage Current	V _R =10V		30	μA
V _F	Forward Voltage	I _F =10mA		0.35	Volts
		I _F =200mA		0.50	Volts

Green Product



DEVICE MARKING CODES:

+

Device Type	Marking	Shipping
RB521S8-30	F	8000/Tape & Reel



Preliminary Datasheet





NOTICE

The information presented in this document is for reference only. Tak Cheong reserves the right to make changes without notice for the specification of the products displayed herein.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Tak Cheong Semiconductor Co., Ltd., or anyone on its behalf, assumes no responsibility or liability for any damagers resulting from such improper use of sale.

This publication supersedes & replaces all information reviously supplied. For additional information, please visit our website <u>http://www.takcheong.com</u>, or consult your nearest Tak Cheong's sales office for further assistance.