

**GLASS PASSIVATED BRIDGE RECTIFIERS**

**REVERSE VOLTAGE – 400 to 1000 Volts  
FORWARD CURRENT – 3.0 Ampere**


**FEATURES**

- Rating to 1000V PRV
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- The plastic material has UL flammability classification 94V-0

**MECHANICAL DATA**

- Polarity : As marked on body
- Weight : 0.05 ounces, 1.52 grams
- Mounting position : Any

**KBP**



KBP		
DIM.	MIN.	MAX.
A	14.25	14.75
B	3.35	3.65
C	10.20	10.60
D	14.25	14.73
d	1.40	1.70
E	1.80	2.20
F	0.80	1.10
G	3.56	4.06
H	0.35	0.55
I	1.22	1.42
J	0.76	0.86
K	2.7 x 45°(Typ.)	
L	-	3°
M	-	2°

All Dimensions in millimeter

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**


Ratings at 25°C ambient temperature unless otherwise specified.

CHARACTERISTICS	SYMBOL	KBP304G	KBP306G	KBP308G	KBP310G	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_C=105^\circ\text{C}$	$I_{(AV)}$	3.0 1.9				A
Peak Forward Surge Current @ $T_j = 25^\circ\text{C}$	$I_{FSM}$					A
8.3ms single half sine-wave @ $T_j = 125^\circ\text{C}$						
Peak Forward Surge Current @ $T_j = 25^\circ\text{C}$	$I_{FSM}$					A
1.0ms single half sine-wave @ $T_j = 125^\circ\text{C}$						
Maximum Forward Voltage at 3.0A DC	$V_F$	1.1				V
Maximum DC Reverse Current at rated Blocking Voltage @ $T_j=25^\circ\text{C}$ @ $T_j=125^\circ\text{C}$	$I_R$	5.0 500				$\mu\text{A}$
$I^2t$ Rating for fusing ( $3\text{ms} \leq t \leq 8.3\text{ms}$ )	$I^2t$	26.5				$\text{A}^2\text{S}$
Typical Junction Capacitance per element (Note 1)	$C_J$	50				pF
Typical thermal resistance (Unit mounted on 30mmx30mmx1mm Copper plate heatsink.)	$R_{\theta JC}$	10				$^\circ\text{C/W}$
	$R_{\theta JL}$	12				
	$R_{\theta JA}$	30				
Typical thermal resistance (without heatsink)	$R_{\theta JC}$	12				$^\circ\text{C/W}$
	$R_{\theta JL}$	18				
	$R_{\theta JA}$	40				
Operation Temperature Range	$T_J$	-55 to +150				$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 to +150				$^\circ\text{C}$


Note: (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

REV. 7, Sep-2012, KBDE06


**FIG.1- FORWARD CURRENT DERATING CURVE**




**FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT**




**FIG.3- TYPICAL JUNCTION CAPACITANCE**




**FIG.4- TYPICAL FORWARD CHARACTERISTICS**



**FIG.5- TYPICAL REVERSE CHARACTERISTICS**



**FIG.6- NON-REPETITIVE SURGE CURRENT**



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.