





VOLTAGE RANGE: 50 ---- 1000V

CURRENT: 1.0 A

Features

- ✧ For surface mounted applications
- ✧ Low leakage
- ✧ Low forward voltage drop
- ✧ High current capability
- ✧ Easily cleaned with Alcohol, Isopropnol and similar solvents
- ✧ The plastic material carries U/L recognition 94V-0

SMA/DO-214AC



Dimensions in inches and (millimeters)

Mechanical Data

- ✧ Case: JEDEC DO-214AC, molded plastic
- ✧ Terminals: Solder plated, solderable per MIL- STD-202, Method 208
- ✧ Polarity: Color band denotes cathode end
- ✧ Weight: 0.002 ounces, 0.064 grams
- ✧ Mounting position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.







Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		GS1A	GS1B	GS1D	GS1G	GS1J	GS1K	GS1M	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current @ $T_L=110^{\circ}C$	$I_{(AV)}$	1.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load $T_J=125^{\circ}C$	I_{FSM}	30							A
Maximum instantaneous forward voltage at 1.0 A	V_F	1.1							V
Maximum reverse current @ $T_A=25^{\circ}C$ at rated DC blocking voltage @ $T_A=100^{\circ}C$	I_R	5.0 50							μA
Typical junction capacitance (Note1)	C_J	15							pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	75							$^{\circ}C/W$
Operating temperature range	T_J	- 55 --- + 150							$^{\circ}C$
Storage temperature range	T_{STG}	- 55 --- + 150							$^{\circ}C$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Thermal resistance from junction to ambient

Ratings AND Characteristic Curves

FIG.1 – FORWARD DERATING CURVE

FIG.2 PEAK FORWARD SURGE CURRENT

FIG.3 – TYPICAL FORWARD CHARACTERISTICS

FIG.4 – TYPICAL REVERSE CHARACTERISTICS

FIG.5-TYPICAL JUNCTION CAPACITANCE

FIG.6-TRANSIENT THERMAL IMPEDANCE


PACKAGE	SPQ/PCS	CARTON SPQ/PCS	CARTON SIZE/CM	CARTON GW/KG	CARTON NW/KG
SMA	5000/REEL	80000	36X30.6X31	12.00	11.00