


SOT-23 Plastic-Encapsulate MOSFETS

20V P-Channel MOSFET

V_{(BR)DSS}	R_{DS(on)Typ}	I_{D Max}
-20V	125mΩ@4.5V	-2.3A
	140mΩ@3.3V	

SOT-23




Features

Trench FET Power MOSFET


APPLICATION

- Load Switch for Portable Devices
- DC/DC Converter

MARKING



Equivalent circuit



PACKAGE SPECIFICATIONS

Package	Reel Size	Reel DIA. (mm)	Q'TY/Reel (pcs)	Box Size (mm)	QTY/Box (pcs)	Carton Size (mm)	Q'TY/Carton (pcs)
SOT-23	7'	178	3000	203×203×195	45000	438×438×220	180000

Maximum Ratings and Thermal Characteristics (TA = 25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V _{DS}	-20	V
Gate-Source Voltage	V _{GS}	±10	
Continuous Drain Current T _A = 25 °C T _A = 70°C	I _D	-2.3	A
		-2.5	
Pulsed Drain Current ¹⁾	I _{DM}	-12	A
Maximum Power Dissipation ²⁾ T _A = 25 °C T _A = 70°C	P _D	1.2	W
		0.9	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-50 to 150	°C
Junction-to-Ambient Thermal Resistance (PCB mounted) ²⁾	R _{thJA}	100	°C/W

Notes

¹⁾ Pulse width limited by maximum junction temperature.

²⁾ Surface Mounted on FR4 Board, t ≤ 5 sec.

The above data are for reference only.



MOSFET ELECTRICAL CHARACTERISTICS

T_a=25 °C unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Static						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250µA	-20			V
Gate-source threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250µA	-0.4	-0.6	-1	
Gate-source leakage	I _{GSS}	V _{DS} = 0V, V _{GS} = ±10V			±100	nA
Zero gate voltage drain current	I _{DSS}	V _{DS} = -20V, V _{GS} = 0V			-1	µA
Drain-source on-state resistance ^a	R _{DS(on)}	V _{GS} = -4.5V, I _D = -3A		70	90	mΩ
		V _{GS} = -3.3V, I _D = -2.0A		78	100	
Forward transconductance ^a	g _f	V _{DS} = -5V, I _D = -2.8A		4.0		S
Dynamic^b						
Input capacitance	C _{iss}	V _{DS} = -10V, V _{GS} = 0V, f = 1MHz		330		pF
Output capacitance	C _{oss}			50		
Reverse transfer capacitance	C _{rss}			45		
Total gate charge	Q _g	V _{DS} = -10V, V _{GS} = -4.5V, I _D = -3A		6.6		nC
Gate-source charge	Q _{gs}			0.8		
Gate-drain charge	Q _{gd}			0.7		
Turn-on delay time	t _{d(on)}			1.4		
Rise time	t _r	V _{DD} = -10V, R _L = 10Ω, I _D = -3A, V _{GEN} = -4.5V, R _g = 3.3Ω		11		ns
Turn-off delay time	t _{d(off)}			12		
Fall time	t _f			18		
				30		
Drain-source body diode characteristics						
Continuous source-drain diode current	I _s	T _C = 25°C			-1.5	A
Body diode voltage	V _{SD}	I _s = -2A		-0.85	-1.2	V

^a) Pulse test: pulse width ≤ 300us, duty cycle≤ 2%

^b) Guaranteed by design, not subject to production testing

Typical Characteristics




Fig1. Typical Output Characteristics




Fig2. Normalized Threshold Voltage Vs. Temperature




Fig3. Typical Transfer Characteristics




Fig4. Drain -Source Voltage vs Gate -Source Voltage




Fig5. Typical Source-Drain Diode Forward Voltage




Fig6. Maximum Safe Operating Area

Typical Characteristics




Fig7. Typical Capacitance Vs. Drain-Source Voltage




Fig8. Typical Gate Charge Vs. Gate-Source Voltage




Fig9. Normalized Maximum Transient Thermal Impedance





Fig10. Switching Time Test Circuit and waveforms


Outline Drawing

SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		
	Min	Typ	Max
A	1.00		1.40
A1			0.10
b	0.35		0.50
c	0.10		0.20
D	2.70	2.90	3.10
E	1.40		1.60
E1	2.4		2.80
e		1.90	
L	0.10		0.30
L1	0.4		
θ	0°		10°

Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Important Notice and Disclaimer

Microdiode Electronics (Jiangsu) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Microdiode Electronics (Jiangsu) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Microdiode Electronics (Jiangsu) assume any liability for application assistance or customer product design. Microdiode Electronics (Jiangsu) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Electronics (Jiangsu).

Microdiode Electronics (Jiangsu) products are not authorized for use as critical components in life support devices or systems without express written approval of Microdiode Electronics (Jiangsu).