


**P.C.B. LAYOUT**

SECTION A-A

**电气性能/Electrical**

参考标准/Standard: UL IEC
额定电压/Rated voltage: 300V 750V
额定电流/Rated current: 20A 24A
使用线径/Wire range: 22-12AWG 2.5mm²
耐电压/Withstanding voltage: AC2000V/1Min
绝缘电阻/Insulation resistance: 500MΩ/DC500V

机械性能/Mechanical

温度范围/Temp.Range: -40° C~+105° C
最大锁紧力矩/Max.Value: 1.2Nm (10.6l b. in)


尺寸/Dimensions

间距/Pitch: 10.0mm
极数/Poles: 2P-24P

材质及电镀/Material

塑件/Housing: PA66, UL94V-0
螺丝/Screws: M4, steel Ni plated
焊脚/Pin header: Brass, 0.8, Tin plated

订购方式:
HOW TO ORDER



	linear dimension(Tolerances Standard GB/T 14486-2008)										≡	—	□	//	⊥	
variable range	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	all	to 5	over 5 to 30	over 30 to 120	over 120 to	
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	比例	第一视角/FIRST ANGLE PROJECTION	
Cixi Dibo Electronics Co.,LTD						名称/NAME	DBT30C-10.0-XXP