






- NOTES:
1. MATERIAL:
HOUSING: HIGHT-TEMP PLASTIC,UL 94-V0,COLOR:NATURE;
COVER: HIGHT-TEMP PLASTIC,UL 94-V0,COLOR:BLACK;
CONTACT: COPPER ALLOY;
LEG: COPPER ALLOY;
 2. PLATING:
CONTACT: GOLD OR TIN PLATED ON NICKEL OVERALL.
LEG: TIN PLATED ON NICKEL OVERALL.
 3. RATING:
CURRENT RATING: 0.5A AC/DC
VOLTAGE RATING: 25V AC/DC
TEMPERATURE RANGE: -25°C~+85°C;
 - 4.PART NO:
- X05A15 L XX X**
- ① ② ③ ④
- ① Series Name :X05A15=0.5 mm Pitch(H=1.5mm)
② Assembly style : L:Low Contact SMT Type U:Upper Contact SMT Type
D:Double-Face Contact SMT Type H:Back-flip Double-Face Contact SMT Type
③ Number of terminals :XX=04-60PIN
④ Plating : G:Gold Flash Over Nickel T:Tin Over Nickel

PIN NO.	DIM. A	DIM. B	DIM. C
14	11.10	6.50	7.57
15	11.60	7.00	8.07
04	6.10	1.50	2.57
05	6.60	2.00	3.07
06	7.10	2.50	3.57
07	7.60	3.00	4.07
08	8.10	3.50	4.57
09	8.60	4.00	5.07
10	9.10	4.50	5.57
11	9.60	5.00	6.07
12	10.10	5.50	6.57
13	10.60	6.00	7.07
15	11.60	7.00	8.07
16	12.10	7.50	8.57
17	12.60	8.00	9.07
18	13.10	8.50	9.57
19	13.60	9.00	10.07
20	14.10	9.50	10.57
21	14.60	10.00	11.07
22	15.10	10.50	11.57
23	15.60	11.00	12.07
24	16.10	11.50	12.57
25	16.60	12.00	13.07


APPLICABLE FFC
TOLERANCE:±0.05

RECOMMEND PCB LAYOUT
TOLERANCE:±0.05

							DSND		DATE		SCALE: N/A	MODEL TYPE: FPC CONNECTOR		
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.:		
△X					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: X05A15LXXX		
△X					4 < L ≤ 16	±0.3			DATE					
△X					16 < L ≤ 63	±0.4			DATE					
MARK	DESCRIPTION		DATE	REVISED	APPROVED	L > 63	±0.5	APPD		DATE	SIZE: A4			
REVISIONS						UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn												1.0g	1/1	A0




- NOTES:
- MATERIAL:
HOUSING: HIGHT-TEMP PLASTIC,UL 94-V0,COLOR:NATURE;
COVER: HIGHT-TEMP PLASTIC,UL 94-V0,COLOR:BLACK;
CONTACT: COPPER ALLOY;
LEG: COPPER ALLOY;
 - PLATING:
CONTACT: GOLD OR TIN PLATED ON NICKEL OVERALL.
LEG: TIN PLATED ON NICKEL OVERALL.
 - RATING:
CURRENT RATING: 0.5A AC/DC
VOLTAGE RATING: 25V AC/DC
TEMPERATURE RANGE: -25°C~+85°C;
 - PART NO:



X05A15 L XX X


① ② ③ ④

- Series Name : X05A15=0.5 mm Pitch(H=1.5mm)
- Assembly style : L:Low Contact SMT Type U:Upper Contact SMT Type
D:Double-Face Contact SMT Type H:Back-flip Double-Face Contact SMT Type
- Number of terminals :XX=04-60PIN
- Plating : G:Gold Flash Over Nickel T:Tin Over Nickel



RECOMMEND PCB LAYOUT
TOLERANCE:±0.05

PIN NO.	DIM. A	DIM. B	DIM. C	PIN NO.	DIM. A	DIM. B	DIM. C
26	17.10	12.50	13.57	44	26.10	21.50	22.57
27	17.60	13.00	14.07	45	26.60	22.00	23.07
28	18.10	13.50	14.57	46	27.10	22.50	23.57
29	18.60	14.00	15.07	47	27.60	23.00	24.07
30	19.10	14.50	15.57	48	28.10	23.50	24.57
31	19.60	15.00	16.07	49	28.60	24.00	25.07
32	20.10	15.50	16.57	50	29.10	24.50	25.57
33	20.60	16.00	17.07	51	29.60	25.00	26.07
34	21.10	16.50	17.57	52	30.10	25.50	26.57
35	21.60	17.00	18.07	53	30.60	26.00	27.07
36	22.10	17.50	18.57	54	31.10	26.50	27.57
37	22.60	18.00	19.07	55	31.60	27.00	28.07
38	23.10	18.50	19.57	56	32.10	27.50	28.57
39	23.60	19.00	20.07	57	32.60	28.00	29.07
40	24.10	19.50	20.57	58	33.10	28.50	29.57
41	24.60	20.00	21.07	59	33.60	29.00	30.07
42	25.10	20.50	21.57	60	34.10	29.50	30.57

							DSND		DATE		SCALE: N/A	MODEL TYPE: FPC CONNECTOR			
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.:			
△X					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.:			
△X					4 < L ≤ 16	±0.3	APPD		DATE		SIZE: A4	X05A15LXXX			
△X					16 < L ≤ 63	±0.4									
MARK	DESCRIPTION		DATE	REVISED	APPROVED	L > 63	±0.5	XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT 1.0g	SHEET 1/1	REVISION A0	
REVISIONS							UNSPECIFIED TOLERANCES								
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn															