



APPROVAL SHEET

Approval Specification	Customer's Approval Certificate
TO:	Checked & Approved by:
Part No.:	Date:
Customer's Part No.:	Please return this copy as a certification of your approval

BEIJING ZHONGXUN SIFANG SCIENCE & TECHNOLOGY CO.,LTD.

Tel: +86-010-58937383
Fax: +86-010-58937263
E-mail: zxsf_sales@163.com
QQ: 3037058772
Website: <http://www.bjzxsf.net> <http://www.sfsaw.com>
Add: No 201, Block A. Building 3. Yongjie Beilu
Yongfeng high-tech industrial base
Haidian District Beijing city



Part No.	:	R915
Pages	:	7
Date	:	2015/9/29
Revision	:	1.0


Prepared by:	王招林
Checked by:	杨宗伟
Approved by:	蒋燕港

History Record

Date	Part No.	Version No.	Modify Content	Remark


Features

- 1-port Resonator
- Ceramic Package for **Surface Mounted Technology (SMT)**
- **RoHS** compatible
- Package size 3.0x3.0x1.25mm³
- Package Code DCC6C
- **Electrostatic Sensitive Device(ESD)**




Application


Typical Low-Power Transmitter Application



Typical Local Oscillator Application




Package Dimensions (DCC6C)



Pin Configuration


2	Input/Output
5	Input/Output
1,3,4,6	Case Ground

Marking




●	Pin 1
R	SAW Resonator
915	Part number

Test Circuit



Equivalent LC Model



Performance

Maximum Rating

Item		Value	Unit
DC Voltage	V_{DC}	± 30	V
Operation Temperature	T	-40 ~ +85	°C
Storage Temperature	T_{stg}	-40 ~ +85	°C
RF Power Dissipation	P	15	dBm

Electronic Characteristics


Test Temperature: 25°C±2°C

Terminating source impedance: 50Ω

Terminating load impedance: 50Ω

Item			Minimum	Typical	Maximum	Unit
Center Frequency	Absolute Frequency	f_c		915.00		MHz
	Tolerance from 915.00MHz	Δf_c		±150		KHz
Insertion Loss(min)		IL		1.2	2.0	dB
Quality Factor	Unloaded Q	Q_U		15069		
	50Ω Loaded Q	Q_L		715		
Frequency Aging	Absolute Value during the First Year	$ f_A $		≤10		ppm/yr
DC Insulation Resistance between Any Two Pins			1.0			MΩ
RF Equivalent RLC Model	Motional Resistance	R_M		4.9	10.0	Ω
	Motional Inductance	L_M		13.0		μH
	Motional Capacitance	C_M		2.54		fF
	Static Capacitance	C_0	2.55	2.85	3.15	pF

Frequency Response



No.	Test item	Test condition
1	Temperature Storage	(1) Temperature: 85°C±2°C , Duration: 250h , Recovery time: 2h±0.5h (2) Temperature: -40°C±3°C , Duration: 250h ,Recovery time: 2h±0.5h
2	Humidity Test	Conditions: 60°C±2°C , 90~95% RH Duration: 250h
3	Thermal Shock	Heat cycle conditions: TA=-40°C±3°C, TB=85°C±2°C, t1=t2=30min, Switch time: ≤3min , Cycle time: 100 times , Recovery time : 2h±0.5h.
4	Vibration Fatigue	Frequency of vibration: 10~55Hz Amplitude:1.5mm Directions: X,Y and Z Duration: 2h
5	Drop Test	Cycle time: 10 times Height: 1.0m
6	Solder Ability Test	Temperature: 245°C±5°C Duration: 3.0s--5.0s Depth: DIP--2/3 , SMD--1/5
7	Resistance to Soldering Heat	(1)Thickness of PCB:1mm , Solder condition: 260°C±5°C , Duration: 10±1s (2)Temperature of Soldering Iron: 350°C±10°C , Duration: 3~4s , Recovery time : 2 ± 0.5h

The graph illustrates a heating cycle with the following phases and data points:

Time (Sec)	Temperature (Deg °C)	Phase / Annotation
0	30	Start
60	150	Pre-heating phase begins
150	170	Pre-heating phase ends
220	260	Max peak (260+0/-5°C)
250	220	Heating phase ends
380	80	End of cycle

Notes

1. As a result of the particularity of inner structure of SAW products, it easy to be breakdown by electrostatic, so we should pay attention to **ESD protect** in the test.
2. **Static voltage** between signal load and ground may cause deterioration and destruction of the component. Please avoid static voltage.
3. **Ultrasonic cleaning** may cause deterioration and destruction of the component. Please avoid ultrasonic cleaning.
4. Only leads of component may **be soldered**. Please avoid soldering another part of component.
5. There is a close relationship between the device's performance and **matching network**. The specifications of this device are based on the test circuit shown above. L and C values may change depending on board layout. Values shown are intended as a guide only.