




**-30V /-6A Dual 2P Power MOSFET**
**General Description**

-30V /-6A Dual 2P Power MOSFET

 Very low on-resistance  $R_{DS(on)}$  @  $V_{GS}=4.5\text{ V}$ 

Pb-free lead plating; RoHS compliant

$V_{DS}$	-30	V
$R_{DS(on),TYP@VGS=10V}$	40.6	m $\Omega$
$R_{DS(on),TYP@VGS=4.5}$	63.8	m $\Omega$
$I_D$	-6	A



Part ID	Package Type	Marking	Tape and reel information
SM4807PRL	SOP8	4807	3000


 100% UIS Tested  
 100% Kg Tested

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	-30	V
Gate-Source Voltage	$V_{GS}$	20	$\pm V$
Continuous Drain Current <sup>A</sup>	$I_D$	$T_A=25^\circ C$	-6.0
		$T_A=70^\circ C$	-5.0
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	-9.6	A
Avalanche Current <sup>G</sup>	$I_{AR}$	-1.9	
Repetitive avalanche energy $L=0.1\text{mH}$ <sup>G</sup>	$E_{AR}$	-4.4	mJ
Power Dissipation <sup>A</sup>	$P_D$	$T_A=25^\circ C$	2
		$T_A=70^\circ C$	1.3
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	$^\circ C$

**Thermal Characteristics**

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	145	217	$^\circ C/W$
Maximum Junction-to-Ambient <sup>A</sup>		Steady State	290	348
Maximum Junction-to-Lead <sup>c</sup>	$R_{\theta JL}$	87	139	$^\circ C/W$



**STATIC PARAMETERS**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	I <sub>D</sub> = -250uA, V <sub>GS</sub> = 0V	-30			V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =-30V, V <sub>GS</sub> =0V			-1 -5	uA
I <sub>GSS</sub>	Gate-Body leakage current	V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±20V			±100	nA
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> = V <sub>GS</sub> I <sub>D</sub> = 250µA	-1.2	-1.8	-2.4	V
R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =-10V, I <sub>D</sub> =-6A		40.6	58.0	mΩ
		V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-6A		63.8	82.9	
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =-5V, I <sub>D</sub> =-6A		48		S
V <sub>SD</sub>	Diode Forward Voltage	I <sub>S</sub> =-1A, V <sub>GS</sub> =0V		-0.72	-1	V
I <sub>S</sub>	Maximum Body-Diode Continuous Current				-6	A

**DYNAMIC PARAMETERS**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> =0V, V <sub>DS</sub> =-15V, f=1MHz		760	927	pF
C <sub>oss</sub>	Output Capacitance			140	172	pF
C <sub>rss</sub>	Reverse Transfer Capacitance			95	113	pF
R <sub>g</sub>	Gate resistance	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz			1.6	Ω

**SWITCHING PARAMETERS**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Q <sub>g</sub> (10V)	Total Gate Charge	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, I <sub>D</sub> =-6A		6.7		nC
Q <sub>g</sub> 4.5V)	Total Gate Charge			3.35		
Q <sub>gs</sub>	Gate Source Charge			2.24		
Q <sub>gd</sub>	Gate Drain Charge			3.2		
t <sub>D(on)</sub>	Turn-On DelayTime	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, R <sub>L</sub> =0.75 Ω, R <sub>GEN</sub> =3Ω		7.5		ns
t <sub>r</sub>	Turn-On Rise Time			6		
t <sub>D(off)</sub>	Turn-Off DelayTime			21		
t <sub>f</sub>	Turn-Off Fall Time			6.75		
t <sub>rr</sub>	Body Diode Reverse Recovery Time	I <sub>F</sub> =-8A, dI/dt=500A/µs		15		ns
Q <sub>rr</sub>	Body Diode Reverse Recovery Charge	I <sub>F</sub> =18A, dI/dt=500A/µs		9.7		nC

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Single Pulse Avalanche capability (Note C)




Figure 10: Maximum Forward Biased Safe Operating Area (Note F)




Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)