







Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 7A AC / DC
- Withstanding voltage: 1500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing: ≤20mΩ

X9396 H X - XX X - N0 XX

- (1) Series No.
(2) Category: H-HSG
(3) Welding Board Angle: Blank-ordinary
(4) Row No.-Pin No.:XX-Single row ;
(5) Plug the Pin & special No.
(6) Material: N0-PA66 94V-0
(7) C-Resistance to glowing filament

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	3.96	8.02	09	31.68	35.74
03	7.92	11.98	10	35.64	39.70
04	11.88	15.94	11	39.60	43.66
05	15.84	19.90	12	43.56	47.62
06	19.80	23.86	13	47.52	51.58
07	23.76	27.82	14	51.48	55.54
08	27.72	31.78	15	55.44	59.50

X9396H-XX-N0-C	Nylon 66 UL 94V-0	X9396T	X9396W
X9396H-XX-N0	Nylon 66 UL 94V-0		
PART N0	Material	Suitable XKB Terminal	Suitable XKB Terminal

For and on behalf of
XKB INDUSTRIAL PRECISION CO., LIMITED
香港星坤工業精密有限公司

	XKB INDUSTRIAL PRECISION CO., LIMITED					ANGULAR	± 5°		
△ X	香港星坤工業精密有限公司					L ≤ 4	± 0.2		
△ X						4 < L ≤ 16	± 0.3		
△ X						16 < L ≤ 63	± 0.4		
MARK	DESCRIPTION				DATE	REVISED	APPROVED	L > 63	± 0.5
REVISIONS								UNSPECIFIED TOLERANCES	
Authorized Signature(s)									

DSND		DATE		SCALE: N/A	MODEL TYPE: X9396H-XX-N0	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm	3.96mm Crimp Style Connectors	
APPD		DATE		SIZE: A4	DWG NO.:	
XKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET	REVISION
				1.0g	1/1	A0