



RoHS

MAPX

MODIFICATION

DRW

DATE



NOTES:

- MATERIAL: SEE "TABLE 1";
- FINISH: SEE "TABLE 1";
- ELECTRICAL :
 - CONTACT CURRENT RATING :
5A (VBUS PIN 1.5A/PIN),
5A (GND PIN 1.25A/PIN MAX), 0.25A/PIN (OTHER PIN).
 - INSULATION RESISTANCE :
100 MEGAOHMS MIN. AT 250VDC.
 - DIELECTRIC WITHSTANDING VOLTAGE :
100VAC MIN.
 - LOW LEVEL CONTACT RESISTANCE :
INITIAL 40mΩ MAX.
AFTER 50mΩ MAX.
- MECHANICAL CHARACTERISTICS :
 - MATING FORCE: 5~20N.;
 - UNMATING FORCE: 8~20N (INITIAL),
6~20N (AFTER 10000 CYCLES);
 - DURABILITY : 10,000 MATING CYCLES.
 - OPERATING TEMPERATURE :-40° C TO +80° C










TABLE 1:

④	Shell	1	Stainless steel	NI PLATING;	T=0.25mm
③	MID PLATE	1	Stainless steel		T=0.15mm
②	Terminal	24	7025	Au:15u" PLATING;	T=0.12mm
①	Housing	3	HIGH TEMP	White	
N.O.	PART NAME	QTY	MATERIAL	DESCRIPTION	REMARK

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.25	X.	±5.°
.X	±0.20	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

深圳市精拓金电子有限公司
Shenzhen Jing Tuo Jin Electronics Co., Ltd.

单位 UNITS	MM	制图 DRAWING	YANG	制图料号 PRODUCT PART NO.				
比例 SCALE	1:1	审核 CHKD	郭治富	产品名称 PRODUCT NO.	USB TYPE C 16PIN			
日期 DATE	2019-11-07	核准 APPD	黄国荣	角法 VIEW		版本 VER		A0

P.C.B LAYOUT