

■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 3A AC / DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing: ≤20mΩ

X2026 H X-2*XX AH-N0 XX

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
② Category: H-HSG
③ Appearance type: Blank-Ordinary
④ Row No.-Pin No.: 2*XX-2*02P~2*20P
⑤ Plug the Pin & special No.:
 A-With Lock; H-High Salient Point
⑥ Material: N0-PA66 94V-0
⑦ Color: Blank-Natural Color

Poles	Dimensions (mm)			Poles	Dimensions (mm)		
	A	B	C		A	B	C
2*02	2.00	9.00	4.50	2*12	22.00	29.00	24.50
2*03	4.00	11.00	6.50	2*13	24.00	31.00	26.50
2*04	6.00	13.00	8.50	2*14	26.00	33.00	28.50
2*05	8.00	15.00	10.50	2*15	28.00	35.00	30.50
2*06	10.00	17.00	12.50	2*16	30.00	37.00	32.50
2*07	12.00	19.00	14.50	2*17	32.00	39.00	34.50
2*08	14.00	21.00	16.50	2*18	34.00	41.00	36.50
2*09	16.00	23.00	18.50	2*19	36.00	43.00	38.50
2*10	18.00	25.00	20.50	2*20	38.00	45.00	40.50
2*11	20.00	27.00	22.50				

X2026H-2*XXAH-N0	Nylon 66 UL 94V-0	X2026T	X2026WV-A.X2026WR-A
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

For and on behalf of
XKB INDUSTRIAL PRECISION CO., LIMITED
香港星坤工業精密有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
△ X					ANGULAR ±5°
△ X					L ≤ 4 ±0.2
△ X					4 < L ≤ 16 ±0.3
△ X					16 < L ≤ 63 ±0.4
△ X					L > 63 ±0.5
REVISIONS					
Authorized Signature(s)					

DSND		DATE		SCALE: N/A	MODEL TYPE: X2026H-2*XXAH-N0
DWN		DATE		VIEW: 	PART NO.:
CHKD		DATE		UNIT: mm	2.00mm Crimp Style Connectors
APPD		DATE		SIZE: A4	DWG NO.:
XKB INDUSTRIAL PRECISION CO., LIMITED					WEIGHT 1.0g
					SHEET 1/1
					REVISION A0