

Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 3A AC / DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance:≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing: ≤20mΩ

X2015 H -2*XX -N0

- ① Series No.
② Category: H-HSG
③ Row No.-Pin No.: 2*XX-2*02P-2*20P
④ Material: N0-PA66 94V-0

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
2*02	2.00	5.90	2*13	24.00	27.90
2*03	4.00	7.90	2*14	26.00	29.90
2*04	6.00	9.90	2*15	28.00	31.90
2*05	8.00	11.90	2*16	30.00	33.90
2*06	10.00	13.90	2*17	32.00	35.90
2*07	12.00	15.90	2*18	34.00	37.90
2*08	14.00	17.90	2*19	36.00	39.90
2*09	16.00	19.90	2*20	38.00	41.90
2*10	18.00	21.90			
2*11	20.00	23.90			
2*12	22.00	25.90			

X2015H-2*XX-N0	Nylon 66 UL 94V-0	X2015T	X2015W
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

For and on behalf of
XKB INDUSTRIAL PRECISION CO., LIMITED
香港星坤工業精密有限公司

	AKB INDUSTRIAL PRECISION CO., LIMITED					ANGULAR	±5°		
△ X	香港星坤工業精密有限公司					L ≤ 4	±0.2		
△ X						4 < L ≤ 16	±0.3		
△ X						16 < L ≤ 63	±0.4		
MARK	DESCRIPTION				DATE	REVISED	APPROVED	L > 63	±0.5
REVISIONS								UNSPECIFIED TOLERANCES	
Authorized Signature(s)									

DSND		DATE		SCALE: N/A	MODEL
DWN		DATE		VIEW: 	X2015H-2*XX-N0
CHKD		DATE		UNIT: mm	PART NO.:
APPD		DATE		SIZE: A4	2.00mm Crimp Style Connectors
					DWG NO.:
		WEIGHT	SHEET	REVISION	
		1.0g	1/1	A0	

XKB INDUSTRIAL PRECISION CO.,LIMITED