

A

B

C

D

E

F

A

B

C

D

E



F

Specifications :

- Voltage rating: 50V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance:≥500MΩ
- Contact resistance: ≤20mΩ
- After environmental testing: ≤30mΩ

X1502 T X-P SN X - X
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series Number
- ② Category: T-Terminal
- ③ Shape: Blank-ordinary
- ④ Material: P-Phosphor bronze
- ⑤ Plating style: SN-Bright tin plating
- ⑥ Plating method: Blank-Stamping before plating
- ⑦ Mold No./Mark/Special No.



X1502T-PSN	Phosphor Bronze	AWG#26-32	1.20mm(Max)	Stamping Before Plating:30u" MIN. Ni; 70u" MIN. Sn	X1502H
PART NO	Material	Wire Range	Insulation O.D.	Finish	Suitable XKB Terminal

For and on behalf of XKB INDUSTRIAL PRECISION CO., LIMITED 香港星坤工業精密有限公司						DSND		DATE		SCALE: N/A	MODEL TYPE: X1502T-PSN				
△ X					ANGULAR	± 5°	DWN		DATE	VIEW: 	PART NO.:				
△ X					4 < L ≤ 16	± 0.3	CHKD		DATE	UNIT: mm	1.50mm Crimp Style Connectors				
△ X					16 < L ≤ 63	± 0.4	APPD		DATE	SIZE: A4	DWG NO.:				
MARK					L > 63	± 0.5									
DESCRIPTION						DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES			XKB INDUSTRIAL PRECISION CO.,LIMITED			
REVISIONS						Authorized Signature(s)						WEIGHT	SHEET	REVISION	
												1.0g	1/1	A0	