

Specifications :

- Voltage rating: 50V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance:≥100MΩ
- Contact resistance: ≤20mΩ
- After environmental testing: ≤40mΩ

X1002 T X-P XX X-X -E

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series Number
② Category: T-terminal
③ Shape: Blank-ordinary
④ Material: P-Phosphor bronze
⑤ Plating style:
V**-All Gold-Plated ; *01-Gold Flash ; *03-3u"
SN-Bright tin plating 70-120u"
SN2-Bright tin plating 120u"Min. Ni : 50u" Min.
⑥ Plating method:
Blank-Stamping before plating
B-Plating before stamping
⑦ Mold No./Mark/Special No.
⑧ Plug the Pin & special No.: E-Have ears

X1002T-PV03-E				Stamping Before Pating:30~50u" Ni:Whole Gold ;3u" Min.	X1002H
X1002T-PV01-E	Phosphor Bronze	AWG#28-32	0.80mm(Max)	Stamping Before Pating:30~50u" Ni:Whole Gold ;Gold Flash	
X1002T-PSN2-E				Stamping Before Plating:50u" Min Ni:120u"Sn Min	
X1002T-PSN-E				Stamping Before Plating:30~50u" Ni:70~120u"Sn	
PART NO	Material	Wire Range	Insulation O,D	Finish	Suitable XKB Terminal

For and on behalf of XKB INDUSTRIAL PRECISION CO., LIMITED 香港星坤工業精密有限公司						ANGULAR	±5°	DSND		DATE		SCALE: N/A	MODEL TYPE: X1002T-PXX -E							
△ X						L ≤ 4	±0.2	DWN		DATE		VIEW: 	PART NO.:							
△ X						4 < L ≤ 16	±0.3	CHKD		DATE		UNIT: mm	1.00 mm CrImp Style Connectors							
△ X						16 < L ≤ 63	±0.4	APPD		DATE		SIZE: A4	DWG NO.:							
MARK						L > 63	±0.5													
DESCRIPTION						DATE	REVISED	APPROVED	L > 63		±0.5		UNSPECIFIED TOLERANCES			XKB INDUSTRIAL PRECISION CO.,LIMITED				
REVISIONS						Authorized Signature(s)							WEIGHT			SHEET			REVISION	
												1.0g			1/1			A0		