



RMSB40B THRU RMSB40M

Voltage Range - 100 to 1000 Volts Current - 4.0 Ampere

GLASS PASSIVATED SURFACE MOUNT BRIDGE RECTIFIERS

Features


- ◆ Glass Passivated Chip Junction
- ◆ Reverse Voltage - 100 to 1000 V
- ◆ Forward Current- 4.0 A
- ◆ Fast reverse recovery time
- ◆ Designed for Surface Mount Application

UMSB



Mechanical Data

Case : JEDEC UMSB molded plastic body
 Terminals : Solderable per MIL-STD-750, Method 2026
 Polarity : Polarity symbol marking on body
 Mounting Position : Any
 Weight : 0.00825 ounce, 0.234 grams



Dimensions in inches and (millimeters)

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	Symbols	MDD RMSB40B	MDD RMSB40D	MDD RMSB40G	MDD RMSB40J	MDD RMSB40K	MDD RMSB40M	Units
Marking Code								
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RMS}	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current	I _{F(AV)}	4						A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	95						A
Maximum Forward Voltage at 4.0 A	V _F	1.3						V
Maximum DC Reverse Current @T _a =25 °C at Rated DC Blocking Voltage @T _a =125 °C	I _R	5.0 200						μA
Typical Junction Capacitance (Note 1)	C _j	50						pF
Typical Thermal Resistance (Note2)	R _{θJA} R _{θJC} R _{θJL}	60 15 25						°C/W
Maximum Reverse Recovery Time (Note3)	t _{rr}	150			250	500		ns
Operating and Storage Temperature Range	T _J , T _{stg}	-55 ~ +150						°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4 V D.C.

2. Mounted on glass epoxy PC board with 4×1.5"×1.5" (3.81×3.81 cm) copper pad areas.

3. Measured with $I = 0.5\text{ A}$, $I = 1\text{ A}$, $I_{rr} = 0.25\text{ A}$.



RMSB40B THRU RMSB40M

Voltage Range - 100 to 1000 Volts Current - 4.0 Ampere

Typical Characteristics

Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current





Fig.6- Typical Transient Thermal Impedance




The curve above is for reference only.



RMSB40B THRU RMSB40M

Voltage Range - 100 to 1000 Volts Current - 4.0 Ampere

Suggested Pad Layout



Dim	Min
P1	5.1
P2	7.1
Q1	1.8
Q2	1.3

Important Notice and Disclaimer

Microdiode Electronics (Jiangsu) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Microdiode Electronics (Jiangsu) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Microdiode Electronics (Jiangsu) assume any liability for application assistance or customer product design. Microdiode Electronics (Jiangsu) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Electronics (Jiangsu).

Microdiode Electronics (Jiangsu) products are not authorized for use as critical components in life support