




Ordering Information:


C2521HM-XP - **
1 2

1.Part No.

2.Color:

(blank):Black

WH:White



SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max



Insulation Resistance: 500MΩ Min

Withstanding Voltage: 1500V AC/minute

Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.50	8.00	8P	17.50	23.00
3P	5.00	10.50	9P	20.00	25.50
4P	7.50	13.00	10P	22.50	28.00
5P	10.00	15.50	11P	25.00	30.50
6P	12.50	18.00	12P	27.50	33.00
7P	15.00	20.50			



CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit Scale Sheet
mm 4:1 1 of 1

Draw BY: LIZQ Approved: GONGYB

General Tolerance

x.x±0.25
x.xx±0.20
x.xxx±0.15



Title :

2.50mm PITCH

HOUSING

DRAW NO : C2521HM-XP

REV
A0

REV	DESCRIPTION	DATE
A0	NEW RELEASE	2013.12.11